

## MITA square

recessed with trim


<sup>EN</sup> Square luminaire housing in die-cast aluminium; extremely slim design; recessed luminaire with trim; optional: blind cover to cover the cut-out available as an accessory; suitable for ceiling thickness of 2-25 mm; surface powder coated; high-gloss reflector with faceted design; energy-efficient LEDs with very good colour rendering

<sup>IT</sup> Corpo illuminante quadrato in pressofusione di alluminio; forma estremamente sottile; apparecchio da incasso con bordo perimetrale; in opzione: copertura cieca per l'inserimento nel vano interno disponibile come accessorio; per soffitti di spessore 2-25 mm; verniciatura a polvere; riflettore ad alta lucentezza con design sfaccettato; LED ad efficienza energetica con elevata resa cromatica

### Quickinfo

3000 K, 4000 K, TW  
 CRI ≥ 80, 3 SDCM  
 UGR ≤ 19 / 65° ≤ 1500 cd/m<sup>2</sup>  
 up to 155 lm/W  
 L95 @ 50 000 h  
 DALI-2  
 reflector (UGR ≤ 19)

### Types



### Colours




### Light distribution



suitable for plaster-board or grid ceilings



DIN EN 12464-1  
 UGR ≤ 19



tunable white  
 2700-6500 K

## Order options

### COLOUR TEMPERATURE

3000K	5
4000K	6
tunable white 2700–6500K*	D

\*DALI-2 DT8

### CONTROL

DALI-2

### MATERIAL COLOUR

<input type="radio"/> traffic white RAL 9016	7
<input checked="" type="radio"/> jet black RAL 9005	8

### LIGHT OPTIC COLOUR

chrome reflector	R
black reflector	B

### LIGHT OPTIC COVER

reflector (UGR ≤ 19)





## Options on request

### COLOUR RENDERING INDEX

CRI ≥ 90

### GRID CEILING MOUNTING

installed in module 600 × 600 mm  
installed in module 625 × 625 mm



## MITA square 200 trim



### DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
13.9 W	3000 K	1950 lm	0 7 4 - 8 3 1 4 :: 3 ■ ■
	4000 K	2160 lm	

## MITA square 360 trim



### DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
30 W	3000 K	4220 lm	0 7 4 - 8 3 1 6 :: 3 ■ ■
	4000 K	4650 lm	
41 W*	3000 K	5490 lm	0 7 4 - 8 3 2 6 :: 3 ■ ■
	4000 K	6060 lm	


\*not for tunable white

## Accessories

### BLIND COVER

TYPE	ORDER CODE
MITA 200 square recessed	0 7 4 - 8 9 1 3 4 1 ■
MITA 360 square recessed	0 7 4 - 8 9 1 3 6 1 ■

## Light distribution



reflector (UGR ≤ 19)  
direct

LUMINOUS FLUX value calculated for  
CRI ≥ 80, colour white, reflector chrome