



## TASK

wall


**EN** Rectangular housing made of aluminium with rounded edges; ultra low-profile design (only 15 mm); surface powder coated; suitable for wall mounting; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; light control via highly reflective reflector material; indirect component with special PCBs with asymmetrical light distribution; for optimum ceiling illumination; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering

**ES** Cuerpo de luminaria rectangular de aluminio con cantos redondeados; perfil extra plano (sólo 15 mm); superficie con recubrimiento de pintura en polvo; apropiada para montaje pared; distribución de luz directa a través de cuerpo LGP (Light Guiding Prism); la luz acoplada lateralmente se orienta hacia abajo por medio de un grabado por láser; orientación luz por medio de un elemento altamente reflectante; proporción indirecta con pletinas propias con distribución de luz asimétrica; para una iluminación óptima del techo; iluminación homogénea; LEDs de alta eficiencia que proporcionan una alta reproducción cromática

### Quickinfo

3000 K, 4000 K  
 CRI  $\geq$  90, 3 SDCM  
 up to 125 lm/W  
 L90 @ 50 000 h  
 DALI-2  
 microprismatic (UGR  $\leq$  16)

### Type



### Colours



### Light distribution



direct  
indirect



asymmetrical ceiling  
illumination

## Order options

<b>COLOUR TEMPERATURE</b>	☼☼
3000K	0
4000K	1

## CONTROL

DALI-2

## MATERIAL COLOUR

- pure white RAL 9010 7
- jet black RAL 9005 8


## LIGHT OPTIC COVER

microprismatic (UGR ≤ 16)


## Options on request

## COLOUR RENDERING INDEX

CRI ≥ 80




## TASK wall



## DIRECT/INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
46W	3000K	↓ 1850/↑ 3530lm	0 5 9 - 2 0 3 2 ☼☼ 3 Z
	4000K	↓ 1970/↑ 3760lm	

## Technical data



**TASK wall**  
46W, 4000K, direct/indirect power

### ROOM VALUES

Room dimensions	5.4 × 4.0 × 2.8 m
Reflection factor	0.7   0.5   0.2
Maintenance factor	0.8
Mounting height	2.25 m

### CALCULATION SURFACE


Surface dimensions	Floor
Surface height	0 m

### GLARE EVALUATION

Table Classification	X=4H   Y=8H   S=0.25H
UGR transversal	≤ 19
UGR axial	≤ 19



## Light distribution



microprismatic  
direct/indirect power

**LUMINOUS FLUX** value calculated for  
CRI ≥ 90, colour white, cover microprismatic