

## TASK angular

suspended

<sup>EN</sup> Rectangular suspended luminaire, consisting of single L-shaped or rectangular elements; Luminaire housing made of aluminium – rounded edges; ultra low-profile design (only 15 mm); surface powder coated; cable suspension, tool-less height adjustment; convenient quick mounting system without tools; incl. transparent feed; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; indirect component with special PCBs for increased luminous flux and maximum ceiling illumination; completely homogeneous illumination; energy-eff. LEDs – very good colour rendering; canopy for through wiring; optional acoustic elements available


□ Corpo illuminante a sospensione di forma rettangolare, composto da singoli elementi a L o rettangolari; Corpo illuminante in alluminio – bordi arrotondati; forma ultrapiatta (solo 15 mm); verniciatura a polvere; cavo regolabile in altezza senza attrezzi; pratico sistema di montaggio rapido senza utensili; incl. cavo di alimentazione; distribuzione della luce diretta con sistema LGP-Body (Light Guiding Prism); luce convogliata lateralmente e direzionata in basso tramite incisione laser; percentuale indiretta con piastre a flusso luminoso potenziato e massima illuminazione del soffitto; illuminazione assolutamente omogenea; LED a risp. energ. – ottima resa cromatica; rosone per cablaggio passante; in opzione elementi acustici disponibile

### Quickinfo

4000 K  
 CRI ≥ 90, 3 SDCM  
 up to 118 lm/W  
 L95 @ 50 000 h  
 DALI-2  
 microprismatic (UGR ≤ 19)

acoustic elements  
 PET felt  
 ♻️ from recycled material  
 up to absorption class A  
 🔥 available as B-s1, d0

### Types



### Luminaire colours



### Acoustic colours




### Light distribution




DiiA® standards  
 251, 252, 253




click-system



microprismatic  
 (UGR ≤ 19)



acoustic elements



CRI ≥ 98  
 XPECTRUM

### Order options

#### COLOUR TEMPERATURE

4000 K

#### CONTROL

DALI-2

#### LUMINAIRE COLOUR

- pure white RAL 9010 7
- jet black RAL 9005 8

#### ACOUSTIC COLOUR

- white W
- marble grey D
- felt grey G
- black L
- special colours p. 992 X

#### LIGHT OPTIC COVER

microprismatic (UGR ≤ 19)



### Options on request

#### COLOUR RENDERING INDEX

CRI ≥ 80  
CRI ≥ 98 XPECTRUM

#### FORM

for other configurations see  
TASK S suspended system



### TASK angular suspended



#### DIRECT / INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
197 W	4000 K	↓ 15200 / ± 8050 lm	059-528313 K


### TASK long angular suspended



#### DIRECT / INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
280 W	4000 K	↓ 22480 / ± 11620 lm	059-528413 K

### Technical data



**TASK** long angular, 280 W, 4000 K, direct/indirect power

#### ROOM VALUES

Room dimensions	5.4 × 4 × 2.8 m
Reflection factor	0.7   0.5   0.2
Maintenance factor	0.8
Suspension height	2.25 m

#### CALCULATION SURFACE


Surface dimensions	3.2 × 1.2 m
Surface height	0.75 m
Average illuminance (E <sub>m</sub> )	> 500 lx
Uniformity (U <sub>0</sub> )	> 0.6

#### GLARE EVALUATION

Table Classification X=4H   Y=8H   S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19



### Light distribution



microprismatic  
direct/indirect power

**LUMINOUS FLUX** value calculated for  
CRI ≥ 90, colour white, cover microprismatic

### Acoustic elements

#### TASK ACOUSTIC inlay

	TYPE	L-W-H (mm)	ORDER CODE
1	TASK angular suspended	1155-1155-30	059-579716 K
2	TASK long angular suspended	1155-2346-30	059-579718 K

